



产品目录

PRODUCT CATALOG

Fiber Channel

FIBERTOP	Part Number	Data Rate	Wavelength(nm)	Tx Power(dBm)	Rx Sen(dBm)	Reach	Connector	Temp.
SFP 1x/2x/4xFC	SFP-SM851F-S5Dx	1.063Gb/s	850	-9 ~ -3	≤-20	550m	Duplex LC	C/I
	SFP-SM852F-S3Dx	2.125Gb/s	850	-9 ~ -3	≤-20	300m	Duplex LC	C/I
	SFP-SM311F-20Dx	1.063Gb/s	1310	-9 ~ -3	≤-23	20km	Duplex LC	C/I
	SFP-SMxx1F-40Dx	1.063Gb/s	1310 / 1550	-5 ~ 0	≤-23	40km	Duplex LC	C/I
	SFP-SM312F-20Dx	2.125Gb/s	1310	-5 ~ 0	≤-23	20km	Duplex LC	C/I
	SFP-SMxx2F-xxDx	2.125Gb/s	1310 / 1550	-2 ~ 3	≤-23	40km	Duplex LC	C/I
	SFP-SM854F-S3Dx	4.25Gb/s	850	-6.5 ~ -0.5	≤-15	300m	Duplex LC	C/I
	SFP-SM314F-10Dx	4.25Gb/s	1310	-6.5 ~ -0.5	≤-17.5	10km	Duplex LC	C/I
	SFP-SMxx4F-40Dx	4.25Gb/s	1310 / 1550	0 ~ +4	≤-17.5	40km	Duplex LC	C/I
SFP+ 8xFC	SFP-MM858F-S3Dx	8.5Gb/s	850	-6 ~ -0.5	≤-10.5	300m	Duplex LC	C/I
	SFP-SM318F-10Dx	8.5Gb/s	1310	-6.5 ~ -0.5	≤-14.4	10km	Duplex LC	C/I
SFP+ 16xFC	SFP-MM85DF-S1Dx	14.025Gb/s	850	-7.8 ~ -0.5	≤-10.5	100m	Duplex LC	C/I
	SFP-SM31DF-10Dx	14.025Gb/s	1310m	-5 ~ -0.5	≤-12	10km	Duplex LC	C/I
	SFP-SM31DF-20Dx	14.025Gb/s	1310m	-5 ~ -0.5	≤-13	20km	Duplex LC	C/I
	SFP-SM55DF-40Dx	14.025Gb/s	1550	-1 ~ +3	≤-14	40km	Duplex LC	C/I
	SFP-CWxxDF-40Dx	14.025Gb/s	1470-1610	-1 ~ +3	≤-14	40km	Duplex LC	C/I
	SFP-DWxxDF-40Dx	14.025Gb/s	ITU-T G.692 C21-61	-1 ~ +3	≤-14	40km	Duplex LC	C/I
SFP28 32xFC	SFP-MM85TF-S1Dx	28.05Gb/s	850	-6.2 ~ +2	≤-10.2	100m	Duplex LC	C/I
	SFP-SM31TF-10Dx	28.05Gb/s	1310	-7 ~ +2	≤-11.6	10km	Duplex LC	C/I

Operating case temperature:C= 0 to +70°C I= -40 to +85°C

FIBERTOP

专业致力于光通信产品的研发、生产、销售、服务，为客户提供高性价比的产品和解决方案，根据客户需求提供个性化产品设计服务。

