




产品目录

PRODUCT CATALOG

40G-100G

	Part Number	Data Rate	Wavelength(nm)	Tx Power(dBm)	Rx Sen(dBm)	Reach	Connector	Temp.
QSFP+ 40G	QFP-MM85FG-S1DC	40Gb/s	850	-7.6 ~ +2.4	≤-9.5	100m	MPO	C
	QFP-MM85FG-S3DC	40Gb/s	850	-7.6 ~ +2.4	≤-9.9	300m	MPO	C
	QFP-SM31FG-02DC	40Gb/s	1310 PSM4	-5.5 ~ +1.5	≤-12.5	2km	MPO	C
	QFP-SM31FG-10DC	40Gb/s	1310 PSM4	-5.5 ~ +1.5	≤-12.5	10km	MPO	C
	QFP-CW31FG-02DC	40Gb/s	CWDM4	-7 ~ +2.3	≤-11.5	2km	Duplex LC	C
	QFP-CW31FG-10DC	40Gb/s	CWDM4	-7 ~ +2.3	≤-13.7	10km	Duplex LC	C
	QFP-CW31FG-40DC	40Gb/s	CWDM4	-5.5 ~ +1.5	≤-12.5	40km	Duplex LC	C
QSFP28 100G	QFP-MM85HG-S1DC	100Gb/s	850	-8.4 ~ 2.4	≤-10.3	100m	MPO	C
	QFP-CW31HG-02DC	100Gb/s	CWDM4	-5 ~ +2	≤-12	2km	Duplex LC	C
	QFP-LW31HG-10DC	100Gb/s	LanWDM DML	-4.3 ~ 4.5	≤-10.6	10km	Duplex LC	C
	QFP-LW31HD-10DC	100 ~ 112Gb/s	LanWDM DML	-4.3 ~ +4.5	≤-10.6	10km	Duplex LC	C
	QFP-LW31HG-30DC	100Gb/s	LanWDM DML	-4.3 ~ +4.5	≤-16.6	30km	Duplex LC	C
	QFP-LW31HG-40DC	100Gb/s	LanWDM EML	-2.5 ~ +6.5	≤-20.5	40km	Duplex LC	C

Operating case temperature:C= 0 to +70°C I= -40 to +85°C

FIBERTOP

专业致力于光通信产品的研发、生产、销售、服务，为客户提供高性价比的产品和解决方案，根据客户需求提供个性化产品设计服务。

