



产品目录

PRODUCT CATALOG

25G SFP28

FIBERTOP	Part Number	Data Rate	Wavelength(nm)	Tx Power(dBm)	Rx Sen(dBm)	Reach	Connector	Temp.
SFP28 25G	SFP-MM85T5-S1Dx	25Gb/s	850	-8.4 ~ +2.4	≤-10	100m	Duplex LC	C/I
	SFP-MM85T5-S3Dx	25Gb/s	850	-8.4 ~ +2.4	≤-11.9	300m(OM4)	Duplex LC	C/I
	SFP-SM31T5-S3Dx	25Gb/s	1310	-6 ~ +2	≤-10.5	300m	Duplex LC	C/I
	SFP-SM31T5-10Dx	25Gb/s	1310	-6 ~ +2	≤-13.3	10km	Duplex LC	C/I
	SFP-SM31T5-20Dx	25Gb/s	1310	-5 ~ +2	≤-14	20km	Duplex LC	C/I
	SFP-SM31T5-30Dx	25Gb/s	1310	0 ~ +6	≤-19	30km	Duplex LC	C/I
	SFP-SM31T5-40Dx	25Gb/s	1310(EML)	0 ~ +6	≤-19	40km	Duplex LC	C/I
SFP28 25G CWDM	SFP-CDxxT5-10Dx	25Gb/s	1270-1370	-7 ~ +2	≤-13.3	10km	Duplex LC	C/I
	SFP-CWxxT5-10Dx	25Gb/s	1470 ~ 1610	-1 ~ +6	≤-14	10km	Duplex LC	C/I
SFP28 25G DWDM	SFP-DWxxT5-10DC	25Gb/s	ITU-T G.692 C21-61	-1 ~ +6	≤-15	10km	Duplex LC	C
	SFP-DLxxT5-10DC	25Gb/s	LanWDM(DML)	0 ~ +6	≤-13.3	10km	Duplex LC	C
	SFP-ELxxT5-40DC	25Gb/s	LanWDM(EML)	0 ~ +6	≤-19	40km	Duplex LC	C
SFP28 BIDI 25G	SFP-BL23T5-S3Dx	25Gb/s	1270T/1330R	-4 ~ +4	≤-13.3	300m	Single LC	C/I
	SFP-BL32T5-S3Dx	25Gb/s	1330T/1270R	-4 ~ +4	≤-13.3	300m	Single LC	C/I
	SFP-BL23T5-10Dx	25Gb/s	1270T/1330R	0 ~ +6	≤-13.3	10km	Single LC	C/I
	SFP-BL32T5-10Dx	25Gb/s	1330T/1270R	0 ~ +6	≤-13.3	10km	Single LC	C/I
	SFP-BL23T5-20Dx	25Gb/s	1270T/1330R	0 ~ +6	≤-13.3	20km	Single LC	C/I
	SFP-BL32T5-20Dx	25Gb/s	1330T/1270R	0 ~ +6	≤-13.3	20km	Single LC	C/I
					Operating case temperature:C= 0 to +70°C I= -40 to +85°C			

FIBERTOP

专业致力于光通信产品的研发、生产、销售、服务，为客户提供高性价比的产品和解决方案，根据客户需求提供个性化产品设计服务。

